



**125 kHz
STANDARD
PROXIMITY***

**13.56 MHz
CONTACTLESS SMART
ISO 14443**

**13.56 MHz
CONTACTLESS SMART
ISO 15693**



XceedID



GE/CASI®



MIFARE®
Secure Sector
Part No. 9551/9558



MIFARE® CSN[†]
(Configurable)
Part No. 9551/9558



HID iCLASS®
CSN only[†]



Infineon my-d®
CSN only[†]



Schlage



LenelProx



MIFARE DESFire™
EV1, (Configurable)
Part No. 8000 Series



MIFARE DESFire™
EV1 with PACSA,
Secure Sector,
Part No. 8000 Series



**Inside
Pictotag®**
CSN only[†]



**XceedID
ISOX™**
CSN only[†]



HID®



AWID®



FIPS 201/PIV II
US Government
(ie Oberthur® and
Gemalto®) must order
PIV compliant readers
SXF1100, SXF2100,
SXF2110, SXF2200,
SXF2210, SXF1500,
SXF1200



DESFire®
CSN only[†]
(Configurable)
Part No. 9574



**Texas
Instruments
Tagit®**
CSN only[†]



ST Micro®
CSN only[†]

† Card serial Number Only (CSN) means NO ability to read data application areas (such as typical programmed internal card number).

Functionality for FIPS 201/PIV II is in default configuration. Part numbers are for standard ISO cards. Additional part numbers available.

* For added security, customers can choose to disable proximity functionality once the transition from proximity to contactless smart cards is complete

GRAY indicates configurable formats, **RED** indicates secure formats.